

BASIC MORTAR

PRODUCT DESCRIPTION

Basic Mortar (sand and cement) is a carefully proportioned 1:4 blend of cement and sand. This material is suitable for general purpose mortar applications including below the damp course and for roof tiles. The mortar can also be used for rendering small patches but is not suggested for large areas.

It only requires the addition of water followed by adequate mixing prior to use.

SUPPLY

Basic Mortar is available from most retail hardware and building supply outlets.

Basic Mortar is pre-packed into easy to handle 20kg multi-walled paper bags.

SPECIFICATION

Basic Mortar is proportioned as a M4 mortar in accordance with Table 11.1 of AS 3700. It has been formulated to achieve a minimum mortar prism compressive strength of 7 MPa at 28 days when mixed with 3.2 litres of water per bag.

All products are manufactured under a third party certified manufacturing and supply quality assurance system to ISO 9001 (BSI Certification No FS 604665).

APPLICATIONS

Basic Mortar is ideal for:

- Use as a topping mix.
- Use as a damp course mortar.
- General purpose grouting.
- Roof tile bedding mortar.
- Patching of renders on strong backgrounds.

Limitations

- Do not use with other binding agents or admixtures.

DIRECTIONS FOR USE

1. Place the required quantity of powder into a wheelbarrow or onto a hard non-absorbent surface.
2. Do not mix more mortar than can be used within one hour.
3. Add water gradually and mix thoroughly to obtain an even colour being careful not to allow any cement to wash away. Add only sufficient water to make a plastic, workable mix.
4. Use the mixed mortar within one hour. Do not allow to stand. Adelaide Brighton Cement does not advocate retempering of mixes with additional water.
5. Allow the mortar to stiffen to the touch before raking or finishing.

6. For patch rendering, the surface must be free of dust, oil and loose materials. Dampen the surface with clean water, but do not soak, prior to applying the mortar.
7. Clean tools and equipment with water immediately after use.

TYPICAL PROPERTIES

Bag content	20 kg
Yield	10.5 l/bag
Coverage	25 standard house bricks when using 10 mm joint
Mix composition (Parts by Volume):	
Cement binder	: 1 part
Sand	: 4 parts
Bulk Density	1500 – 1700 kg/m ³
Bond strength when using:	
-Clay	≥ 0.20 MPa
-Masonry	≥ 0.20 MPa
In-house Compressive Strength Mortar Prisms (16% water addition)	
7 days	≥ 5 MPa
28 days	≥ 7 MPa

HANDLING AND STORAGE

Manual handling of bag products without due care and attention may result in personal injury. Unless you have been trained in manual handling methods it is suggested that you share the load with another person.

Basic Mortar can be stored for up to six months provided it is stored in a dry place, off of the ground and protected from ingress of moisture. Ingress of moisture can occur due to rain, spillage of liquid (on or around the product) or a high humidity climate. Such exposure will degrade the performance of the product.

SAFETY INFORMATION

For safety information refer to the Safety Data Sheet for Basic Mortar.

CONTACT POINTS

For further information, contact the Sales and Marketing Department at:

Adelaide Brighton Cement Ltd
 ABN 96 007 870 199
 62 Elder Road
 BIRKENHEAD SA 5015

Telephone: 08 8300 0300

Facsimile: 08 8341 1591

Web Site: www.adelaidebrighton.com.au

DISCLAIMER

While the information in this Product Data Sheet has been prepared in good faith, Adelaide Brighton Cement Limited does not warrant that the information is accurate, complete or up to date. Each user of any information, or any product referred to, in this Product Data Sheet must:

- determine whether the information or product is suitable for their purpose;
- assess and control any risks associated with the information or product; and
- obtain professional advice in relation to the use of the information or product.

Failure to do so may result in serious damage or injury.

To the extent permitted by law, Adelaide Brighton Cement Limited:

- excludes all representations, warranties and guarantees in relation to any information in this Product Data Sheet; and
- will not be liable for any direct, indirect, consequential, incidental, special or economic loss (including but not limited to any loss of actual or anticipated profits, revenue, savings, production, business, opportunity, access to markets, goodwill, reputation, publicity, or use) arising from any use of or reliance on any information in this Product Data Sheet.